

PRODUCT DATASHEET

AGL Secondary
Connector Kits
KD503 & KD503R



FAA AC 5345-26, L-823 Class B

KD503-series (plug)







KD503 connectors have been industry requirement for over 30 years. They are designed for a fast-and-easy watertight connection between the secondary cable and the series isolating transformer. This connector is silicon and used with two single core wires. Connector is fast to install, approx. 1min. KD 503 connectors are FAA certified.

- Superior isolation resistance by thermoplastic elastomer (TPE)
- Nominal rating: 20 A and 600 V
- Wire diameter 2,8 8,0 mm (0.110 0.314 inches) x 2
- Conductor size 1,5 6 mm2 (16 10/8 AWG)
- ROHS compliance with EU directive NO2002/95/EC

KD 503 (Plug) and KD 503R (Receptacle) are packed and delivered in kit including all the necessary parts for making the assembly on secondary cable. Each secondary connector kit contains components for a plug or a receptacle.







Dimensional data

EFLA Type	Туре	Conductor Size	AWG	Wire Diameter
KD503	Plug	1.5-2.5 mm ²	16-14	2.8-4.0 mm, 0.110-0.157"
KD503.1	Plug	4.0-6.0 mm ²	12-10/8	3.8-5.5 mm, 0.149-0.216"
KD503.2	Plug	4.0-6.0 mm ²	12-10/8	2.8-3.4 mm, 0.110-0.133"
KD503.3	Plug	4.0-6.0 mm ²	12-10/8	5.0-8.0 mm, 0.196-0.314"
KD503/R	Receptacle	1.5-2.5 mm ²	16-14	2.8-4.0 mm, 0.110-0.157"
KD503R.1	Receptacle	4.0-6.0 mm ²	12-10/8	3.8-5.5 mm, 0.149-0.216"
KD503.2	Receptacle	4.0-6.0 mm ²	12-10/8	2.8-3.4 mm, 0.110-0.133"
KD503R.3	Receptacle	4.0-6.0 mm ²	12-10/8	5.0-8.0 mm, 0.196-0.314"

Outline





Suggested crimping tools

EFLA recommends these following tools:

Manual crimping tools:

Elpress DKB 0760

Electrical crimping tool:

Elpress PVL 130S - RB0560



EFLA is the world's leading supplier of seamless power and communication products for airfield ground lighting circuits. With more than 30 years experience in the field, it develops, manufactures and sells globally-certified series isolation transformers, connector kits and prefabricated cable leads. The company's components meet the highest qualifications in materials and electrical design to withstand challenging installation in underground pits and cans and direct underground installation. Headquartered in Porvoo, Finland, EFLA supplies products to international airports around the world.

^{*} KD503 series weights 50 g/pc